TopGROUT .SP

SWIMMING POOL GRADE TILE GROUT

TOP GROUT SP Tile Grout is a two part UV rated mortar. With both anti-acid and anti-bacterial functions, it can be used for grout, adhesive and wall finish. SP is waterproof and extremely resistant to chemicals, with a high mechanical strength that doesn't crack during hardening. These qualities make it the perfect option for swimming pools, and its durability is unsurpassed . . It has been developed to provide a single solution for wall and floor grouting that's easy and quick to use, whilst still providing the perfect finish to any project. Rapid-setting with strength and flexibility, TOPGROUT provides ultimate colour consistency, complete with antimicrobial protection.



APPLICATION FIELD

- Outdoor Surfaces
- Floor and Wall tiles
- Bathrooms, Tubs
- Showers
- Swimming Pools
- Kitchen Countertops and Backsplashes
- Terraces and Balconies
- Steam Rooms
- For Porcelain, Ceramic, Marble Natural Stones, Granite
- Tile grout ideal for swimming pool, spa, steam room, and sauna

FEATURES

- Resist to chemical agents used in swimming pool such as chlorine and cleaning agents
- Resist to water pressure in swimming pools
- Resist to high temperature in steam rooms and saunas
- It's recommended for joint width 2 to 10 mm without crack
- Able to stand up to harsh chemicals and constant exposure to water.
- Available in all std colours (Contact OBS support)
- Extremely durable
- Anti fungal

engineered to perfo

PROPERTIES

Compressive strength	30 N/mm2
Bonding Strength	5 N/mm2
Temp. Resistance	- °40C to °100+C
Pot life	30 minutes
Setting time	8 hours
Complete curing	24 hours
Application temperature	: °5+C to °45+C
VOC	≤50g/L

APPLICATION

Substrate preperation

The joints should be clean and dry before grouting. Clean and remove any particles or contaminations remaining in the joints in order to ensure a good grout adhesion and the color uniformity. Avoid using the product in swimming pools when there is direct sunlight. It is recommended to have a shade to help reducing the heat.

Mixing

Mix in a clean container by slowly adding the powder component to the liquid component and mixing with low speed drill and mixing paddle. Gradually add the powder to the mixing liquid while the drill is running. Pot life is 90 minutes @ °28C.

INSTALLATION

Apply to tile joints with squeegee, brush or sponge. Best result can be obtained by filling joints with grout using a hard rubber float working diagonally across the grout joints. All excess grout should be removed with the same rubber float without any delay. However, it is important to allow the grout to firm in the Top-grout is a cement and polymer based water resistance grout that ensures good working quality and permanent joint which is non toxic, odorless.

COVERAGE

1 Kg of Top Grout SP will cover approximately 4m using standard tiles (152mm x 152mm) spacing of tiles .However coverage depends on size and joint acquiring its initial set before any further cleaning.

GROUT CLEANING

When grout is complete use a clean dry cloth and polishes the tiles. Scrubbing the floor with hot water and soap is the best method.

PACKING : TWO PACK (15 KG + 5L)

engineered to perform

Organix Building System LLC
Dubai – United Arab Emirates
Email : info@organixbs.com
www.organixbs.com