INTEX 108

Intergral Waterproofer

PREVENTS WATER PENETRATION OF CONCRETE & MORTAR



INTEX is a high performance latex designed for multipurpose waterproofing system for concrete which enhances water and abrasion resistance. INTEX Integral Water proofer is formulated to provide long term water protection to mortar, concrete and rendering. It features improved workability and strength, anti-corrosion properties and is suitable for all applications where resistance to water damage is essential.

INTEX Integral Waterproofer is suitable for all applications where resistance to water damage is necessary including external rendering and pointing, roof areas and structures below ground level.

FEATURES & BENEFITS

- Avoids water condensation. it allows the passage of air. Resistant to aggressive of chemicals.
- Is non Toxic, suitable and recommended for water tanks .
- Increase concrete strength
- Becomes an integral part of the concrete
- Negligible influence on air entrainment
- Not a vapor barrier - allows concrete to breathe
- No corrosive effect on reinforcing metal

USAGE

Waterproofs and plasticises mortar for :-

- Retaining walls
- External or basement renderings
- Floor and roof screeds
- Tanks.

engineered to perform

PROPERTIES

Appearance	White Liquid
Specific Gravity	1.01@20°C
Solid	50 %
PH	9 –5
Stabilization	Non-iconic
Freeze thaw stability	Good
Mortar workability	1 Hour

**10% tolerance apply.*

APPLICATION AND MIXING

For rendering, concreting swimming pools, tanks etc. 250ml Integral Waterproofer to 25Kg cement. For screed use 1 Integral Waterproofer to 30 parts water. Shake well before use; add to the gauging water in the approximate mix ration not exceeding the ration stated. Re-plastering should be carried out as long as possible after the insertion of a remedial damp-proof course. Ideally the new plaster should be applied to surface-dry walls, but in any case a drying period of at least 14 days should be allowed between installations and re-plastering wherever possible.

COVERAGE

250 - 500ml per 25kg cement

PACKING

4 , 20 Ltr Pails/Jerry Cans

HEALTH & SAFETY INSTRUCTION

Non Hazardous. if ingested seek medical advice.

This data is provided in the belief that it is accurate within generally accepted standards and is provided for the information of qualified personnel. It does not constitute an offer by the manufacturer, nor does the manufacturer warrant or guarantee its accuracy or completeness in describing the describing the performance or suitability of the various products. The users therefore should make their own determination in using the product of the data contained herein for any application.

STORAGE AND TRANSPORTATION: INTEX, when stored on pallets in dry, cool area from moisture and direct sunlight, has a shelf life of 12 months. The liquid Component Bmust not freeze.

Organix Building System LLC
Dubai – United Arab Emirates
Email : info@organixbs.com
www.organixbs.com